

ESPRIMO Mobile V5555

Issue January 2009

Pages 3

The ESPRIMO Mobile V5555 is your gateway to professional mobile working. It is the professional companion for the price-conscious, casual user. This notebook is the ultimate balance of valuable performance and best-in-class mobility at very attractive prices.

You have the brilliant large 15.4-inch widescreen display for a maximum viewing comfort and an ergonomic full-size keyboard. Ideal for users working both on the road and in the office, it features a built-in super multi DVD writer and LAN. The Wireless LAN module offers unlimited freedom of connectivity wherever you are. With the optional built-in 3G/UMTS, the ESPRIMO Mobile V5555 gives access to your data, even if the nearest hot spot is out of reach.

Mobility

Valuable mobility at reasonable price

- Excellent price / performance ratio fits suiting all budgets
- Ready configured and constantly enhanced with latest technology

Convenient technology for mobile working

- Power-saving Intel® Processors
- Ideal connectivity through built-in Wireless LAN and LAN
- Ease of use through built-in super multi DVD burner

Robustness on the move

- German quality standards
- RoHS compliant for environmental friendly working
- Award-winning best-in-class manufacturing
- Mechanical and function stability through extensive quality tests

Ergonomics and flexibility in- and outside the office

- Enjoy the viewing quality of brilliant 15.4-inch WXGA TFT display
- Full-size keyboard for ergonomic working
- 3 x USB (2.0) ports for easy connectivity to all peripherals and external storage devices



System	ESPRIMO Mobile V5555
Processor Intel® Celeron® Processor (Socket P) Second level cache Front side bus (FSB) Intel Pentium Dual Core Processor Second level cache Front side bus (FSB) Intel® Core™ Duo Processor Second level cache Front side bus (FSB) Intel® Core™2 Duo Processor (Socket P) Second level cache Front side bus (FSB)	550 (2.00 GHz) 1 MB 533 MHz up to T2390 (1.86 GHz) 1 MB 533 MHz Up to T5850 2 MB 667 MHz Up to T7300 4 MB 800 MHz
Chipset Northbridge Southbridge	SiS M672 SiS 968
Memory DIMM slots (667 MHz support) DDR2-667 SDRAM	2 Up to 4 GB
BIOS BIOS Flash EPROM	Phoenix First BIOS
Interfaces Express card 34/54 USB 2.0 VGA Modem RJ-11 LAN RJ-45 Audio-in (line-in / microphone) Audio-out (line-out / headphone) DC-in Kensington Lock	1 3 1 optional 1 1 1 1 1
Modem on board 56K V.90 modem MDC1.5	optional
LAN on board built-in 10/100/1000 Mbps Fast Ethernet LAN (SiS196)	x
Wireless Technologies (WLAN) Import and usage according to country-specific regulations. Dual band antenna Atheros b/g integrated UMTS/HSUPA Option GTM378 - 7.2Mbit/s download also supported are GPRS and EDGE or higher	x Optional
Audio Stereo speakers Sound chip Internal microphone	x Realtek ALC268 x
Keyboard and pointing device Keyboard Touchpad Status LED	87 keys, 19mm pitch, 2.5mm key stroke with two mouse buttons
Graphics SiS Mirage 3+ Graphics, 64-256 MB shared memory	x
Display 15.4-inch TFT WXGA / 1280 x 800 pixel non-glare display, (glare optional) Max. resolution for external displays	x Up to 1920 x 1440 / true color / 60 Hz
Hard disk drives (internal) * S.M.A.R.T. 80 GB S-ATA 150 (5400 rpm) 120 GB S-ATA 150 (5400 rpm) 160 GB S-ATA 150 (5400rpm) 250 GB S-ATA 150 (5400rpm) * 1 Gbyte equals one billion bytes, when referring to hard disk drive capacity; accessible capacity may vary, also depending on used software and tool.	- x x x x
Fixed drives Super Multi DVD writer (incl DVD RAM, 8x double layer support)	x
Manageability Please refer to http://www.fujitsu-siemens.com/solutions/it_infrastructure_solutions/manageability/featurefinder.html	
Supported Standard WMI / CIM / WBEM PXE BootP	- x -
Security Physical security Kensington Lock support System Security Norton Internet Security Symantec User Security User and supervisor BIOS password	x x x

* for made4you customizing projects only

Power supply 1st Li-Ion battery 6 cell, 4800 mAh (53 Wh) First battery * (Mobile Mark 2002) [up to] AC adapter 20V/90W Adapter Rated voltage (AC input) 100 - 240 V Rated frequency 50 - 60 Hz DC output 20 V, 4.5 A * Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage. ** for made4you customizing projects only	x 2 h 40 min x
Operating temperatures Relative humidity (non-condensing) Ambient temperature	20% - 85% 5° - 35° C
Dimensions / Weight Dimensions (H x W x D) Weight* * Weight may vary depending on actual configuration	39 x 360 x 260 mm 2.7 kg
Certificates CE Marking R&TTE RoHS WHQL	x x x x
Operating System Microsoft Windows Vista™ (XP drivers available for download) Microsoft Windows Vista® Business/ Microsoft Windows XP® Professional TwinLoad	 x x
Software (compatibility / preinstalled) Adobe Acrobat Reader Driver and Utility DVD (DUDVD) Easy Guide on-line user documentation Nero Norton Internet Security (incl. Firewall) 90days	 x x x x x
Accessories (order number) AC-adapter Case Battery Memory 2 GB-667 Memory 1 GB-667 http://www.fujitsu-siemens.com/accessories/	S26391-F321-L400 Value case S26391-F119-L50 First Li-Ion battery 6 cells/ 5200 mAh , 56.1 Wh for up to 2.5h battery runtime S26391-F6120-L470 S26391-F6120-L482 S26391-F6120-L481

This Data Sheet describes the highest configurations. The product is offered in fixed configurations which vary from country to country and edition to edition.